



IP CAMERA HS-T077SG

- Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
- 2MP (1920 × 1080)
- 50 ~ 70 M IR night view distance
- 3 DNR, TWDR, HLC, BLC, Digital Defog, Smart IR
- ICR auto switch, true day / night
- Built-in micro SD card slot, up to 128GB
- Support ROI coding
- Support three streams
- Two-way audio, built-in MIC
- IP67 ingress protection
- Intelligent analytics: abnormal video signal detection, line crossing detection, region intrusion detection, face detection, face capture

RoHS **CE** **FC**





HS-T077SG

Camera	
Image Sensor	1 / 2.8 " CMOS
Image Size	1920 × 1080
Electronic Shutter	1 / 25 s ~ 1 / 100,000 s
Min. Illumination	0.005 lux@F1.6,AGC ON; 0 lux with IR 0.0028 lux@F1.2,AGC ON; 0 lux with IR
Lens	EVF 2.8 ~ 12 mm @F1.4
Horizontal view Angle	103° ~ 32°
IR Distance	50 ~ 70 m
WDR	120dB
Day & Night	ICR auto switch
BLC	YES
HLC	YES
Digital Defog	YES
Digital DNR	3 DNR

Image	
Video Compression	Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile / Main Profile / High Profile
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1 (704 × 480), 480 × 240, CIF (352 × 240)
Main Stream (S1)	1080P / 720P @30fps
Sub Stream (S2)	720P / D1 / CIF @30fps
Third Stream (S3)	D1 / 480 x 240 / CIF @30fps
Bit Rate	64 Kbps ~ 6 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately

Audio	
Audio Compression	G.711A / U
Two-way audio	YES

Interfaces	
Network	RJ45
Video Output	CVBS output (BNC × 1)
Audio line in	1CH
Audio line out	1CH
Alarm Input	1CH alarm input
Alarm Output	1CH alarm output

Storage	
SD card	Built-in micro SD card slot; up to 128GB
Network remote storage	Yes
Hardware Reset	Yes

Intelligent Analytics (Smart Events)

Perimeter Protection	Line crossing, region entrance/exiting/intrusion (human/motor vehicle / non-motor vehicle classification)
Target Counting	Line crossing human /motor vehicle/non-motor vehicle counting
Exception Detection	Scene change, video blur and video color cast detection
Face Detection	Face detection and face capture
General Intelligence	Crowd density detection, heat map, object abandoned / missing detection (These are being developed and coming soon.)

Functions

Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF, GB-T/28181-2011
Smart Alarm	Motion detection; Sensor alarm; SD card error; SD card full; IP address conflict; Network disconnection
General function	Watermark, IP address filtering, video mask, heartbeat, password protection, non-photosensitive switch, image distortion correction
PoE	Yes, IEEE802.3af

Others

Power Supply	DC12V / PoE
Power Consumption	< 12W
Operating Environment	- 30 ° C ~ 60 ° C (-22° F ~ 140° F) Humidity: less than 95 % (non-condensing)
Dimensions	279.5 x 100.3 x 88.9 mm
Weight	Approx. 1040g
Installation	Ceiling mounting (wall mounting available with the junction box and bracket)
Ingress Protection	IP67

Accessories



B624TV



B625



B615



B616